



Electronic Personal Dosemeter GRAETZ ED150

with dose rate indication and alarm functions


- PTB-approved¹⁾ dosimeter for measuring gamma radiation and X-rays for the dose equivalent H_p (10)
- detector: energy compensated GM-tube
- optimal reading of measured values by digital indication on an especially shaped LC-display
- dose rate indication upon keystroke
- reliable and safe measurement of radiation in front of the user's body (detection of a solid angle of 180°)
- switchable acoustic single-pulse indication
- menu-driven user navigation
- storage of dose value and set parameters also during battery change
- 4 preset alarm thresholds for dose: 200 μ Sv, 500 μ Sv, 1000 μ Sv, 2000 μ Sv
- dose rate: 7,5 μ Sv/h, 25 μ Sv/h, 40 μ Sv/h, 300 μ Sv/h
- Remark: upon request adjustment of customer required alarm thresholds by GRAETZ
- high reliability by continuous self control and test function
- small and handy metallized housing made of high impact-proof plastic, easy to decontaminate, protection class IP67
- power supply by 3 pcs. Lady cells LR1 1,5V
- operating life approx. 1 year with one battery set at ambient background radiation



Technical Data

Measuring ranges:	
– dose	0,1 μ Sv – 10 Sv
– dose rate	1 μ Sv/h – 1,5 Sv/h
– PTB-approved dose ¹⁾	10 μ Sv – 1 Sv
Energy range:	55 keV – 3 MeV
Dose alarm thresholds:	4 preset values in the range of 1 μ Sv – 10 Sv
Dose rate alarm thresholds:	4 preset values in the range of 1 μ Sv/h – 1,5 Sv/h
Temperature range:	-20 °C up to + 60 °C
Dimensions / Weight:	(136 x 40 x 17) mm approx. 160 g
PTB – Approval No.:	23.52 / 04.01
German Fire Brigades Approval No.:	DW/FW/IdF 040411

¹⁾ PTB-approved measuring range for measurements specifically demanded by German regulations



GRAETZ Strahlungsmeßtechnik GmbH

Westiger Straße 172 · D-58762 Altena / Germany
Postfach 81 00 · D-58754 Altena / Germany
Phone +49-2352- 70070 · Fax +49-2352-700710
E-Mail: info@graetz.com
Website: www.graetz.com