## **UV Panel Series**



## OVERHEAD, 12-72 UV LED, Normal/High UV Intensity, White LED

- Use Nichia UV LED and specified UV lens
- Normal / High UV Itensity (6000/9000 uW/cm²)
- UV / White LED Switch
- Expand the length up to 1200mm
- IP65 Classified
- 3 Years free warranty and CE marked

UV - Panel series adopt the original Nichia UV LED as light source, no fan design, smart but rugged enough for industrial use.

It can be working continuously with low heat, it can completely substitute of the traditional Mercury Vapor / HID blubs.

UV - Panel could work in bad environment due to its well designed power supply. If the AC voltage beyond the normal range, the lamp will shut down automatically to protect the expensive LEDs, won't be light on until the voltage come to normal.



12 UV LED 4 White LED



36 UV LED 12 White LED

## Specification:

UV Intensity:	6000 or 9000uW/cm <sup>2</sup>
UV Coverage Area:	300mm × 250mm (The length can be expanded) (38cm, UV Intensity >1,000uW/cm²)
Visible Light @ UV	≤ 3 lux
Power:	115-240 VAC / 50-60 Hz ( Universal )
Power Consumption :	40W
Weight:	4.85Lb (2.2 Kg)
Dimension:	9"×8.3"×3.5" 230×212×90mm (L×W×H)

WenZhou LuCheng NDT Equipment Corp.

Manufacturer of NDT equipments RM.308, Kang Yuan South Building XinCheng Road, 325000 WenZhou, P.R.China. Tel.:0086-577-88293040 Fax:0086-577-88259689 Web:www.Lcndt.net E-mail:Lcndt@163.com