

ND-3000



- FIVE RANGE 0-10 R/hr DUSTPROOF RUGGED SURVEY METER
- REGULATED LOW AND HIGH VOLTAGES
- TWO HALOGEN QUENCHED ENERGY COMPENSATED GM TUBES
- RANGES 0-10,000, 0-1000, 0-100, 0-10, 0-1 mR/hr and 0-100,000, 0-10,000, 0-1000, 0-100, 0-10 uSv/hr
- METER DIAL IN BOTH mR/hr AND uSv/hr
- USES TWO "D" CELL BATTERIES
- ENERGY RESPONSE WITHIN 20% FROM 80-2000 KeV GAMMA AND X-RAY
- INDIVIDUAL CALIBRATION POTENTIOMETERS FOR EACH RANGE
- SATURATION IN EXCESS OF 1000R/hr WHEN CALIBRATED AND MAINTAINED PROPERLY
- RUGGED TWO PIECE NYLON REINFORCED FIBERGLASS CASE
- 3.5" RUGGED METAL METER MOVEMENT
- 4.4"W x 7.75"L X 6.25"H INCLUDING HANDLE
- 3 POUNDS, 14 OUNCES WITH BATTERIES
- Optional [ND-3000A](#): The ND-3000 with Audio