

## **ND- 2000 C**



**Three Range Dustproof Radiographic Survey Meter  
Rugged Two Piece Nylon Reinforced Case and Handle**

**LCD Display**

**Display Available in mR/hr and uSv/hr**

**Gamma and X-Ray From 80-2000 KeV Within 20%**

**Saturation in excess of 1000R/hr when calibrated and maintained properly**

**Halogen Quenched, Energy Compensated GM Tube, Effective Length and Diameter: 0.625" x 0.194", Wall Thickness: 90 mg/cm<sup>2</sup>**

**Individual Calibration Potentiometers for each range**

**3lbs, 15ozs with batteries**

**4.4" W x 7.75" L x 6.25" H, including handle**

**Regulated High and Low Voltages**

**Bright 2.47 Volt Dosimeter Charger Viewing Lamp**

**Operates on two "D" Cell Batteries**

**Operating Temperature: -20 to 50 °C (-4 to 122 °F), Humidity: Non-Condensing 95%**

**Rugged Two Piece Nylon Reinforced Case**

**Option: ND-2000C LED: Uses white LED for Dosimeter Charger Viewing light source**  
**CE**

**NDS**   
**PRODUCTS**

 **MARQUES  
& CIA**

**EQUIPAMENTOS PARA ENSAIOS E INSPEÇÃO**

 (19) 99768.8232  [www.cmarques.com.br](http://www.cmarques.com.br)

 [cmarques@cmarques.com.br](mailto:cmarques@cmarques.com.br)