

PORTABLE X-RAY BETATRON



7.5MeV Model
For illustration purposes only

PORTABLE X-RAY BETATRON SYSTEMS

PIPELINE CRAWLERS • BETATRON PORTABLE X-RAY • DIGITAL RADIOGRAPHY

JME portable Betatron systems are a range of compact circular electron accelerators producing a high energy directional X-Ray beam. The Betatron systems are easy to assemble, operate and maintain. They contain no moving parts or cooling liquids so maintenance required on the systems is minimal. They are capable of producing radiographs of very high contrast, sensitivity and resolution allowing operators to meet the tightest inspection standard.

JME offer 5 systems within the Betatron range each with a different maximum energy, the outputs are 2.5, 6, 7, 7.5 and 9MeV. The energy output on all systems is variable from 2MeV through to the maximum energy and adjustments can be made in 0.1MeV increments. The systems offer cost savings and a greater degree portability when compared with a Linac generators and provide greater flexibility for more mobile inspection tasks.

FEATURES

- Completely Portable
- Output energy selectable up to 9 MeV*
- Excellent sensitivity and resolution
- Penetrates upto 11.81 inch's (300mm) of steel, 39.37 inch's (1m) concrete*

*Dependent on Model

AVAILABLE MODELS



2.5MeV Portable X-Ray Betatron



6MeV Portable X-Ray Betatron



7.5MeV Portable X-Ray Betatron



9MeV Portable X-Ray Betatron

PROUDLY SUPPLYING THE NDT INDUSTRY FOR OVER 30 YEARS



JME
ADVANCED INSPECTION SYSTEMS

CALL OUR SALES TEAM FOR MORE INFORMATION

+44 (0)1502 500969

JME LTD. ELECTRON HOUSE, OLD NELSON STREET
LOWESTOFT, SUFFOLK NR32 1EQ UNITED KINGDOM

FIND JME ONLINE...

www.jme.co.uk

f /JMElimited | t @JME_NDT | in jme-advanced-inspection-systems

TECHNICAL SPECIFICATIONS

PXB 2.5

Peak X-ray Output	2.5 MeV
Dose Rate at 1m (3.3ft)	>0.7R/minute
Focal Spot Size	0.2 x 2.0 mm
Duty Cycle Radiation Beam	75% per hour
Beam Coverage	350 x 350mm @ 1m
Radiographic Sensitivity	Down to 1%
Supply Voltage	Single-phase, 110V or 220V, 50/60Hz
Power Consumption	1.0kW (4.5A @220V, 9A @ 110V)

PXB 6

Peak X-ray Output	2 to 6 MeV
Dose Rate at 1m (3.3ft)	>3R/minute
Focal Spot Size	0.3 x 3.0 mm
Duty Cycle Radiation Beam	75% per hour
Beam Coverage	250 x 250mm @ 1m
Radiographic Sensitivity	Down to 1%
Supply Voltage	Single-phase, 110V or 220V, 50/60Hz
Power Consumption	2.0kW (9A @220V, 18A @ 110V)

Single or Three Phase available upon request

PXB 7.5

Peak X-ray Output	2 to 7.5 MeV
Dose Rate at 1m (3.3ft)	>5R/minute
Focal Spot Size	0.3 x 3.0 mm
Duty Cycle Radiation Beam	75% per hour
Beam Coverage	250 x 250mm @ 1m
Radiographic Sensitivity	1%
Supply Voltage	Single-phase, 110V or 220V, 50/60Hz
Power Consumption	3.0kW (13.6A @220V, 27A @ 110V)

Single or Three Phase available upon request

PXB 9

Peak X-ray Output	2 to 9 MeV
Dose Rate at 1m (3.3ft)	>20R/minute
Focal Spot Size	0.3 x 3.0 mm
Duty Cycle Radiation Beam	50% per hour
Beam Coverage	250 x 250mm @ 1m
Radiographic Sensitivity	1%
Supply Voltage	3-phase (220V/380V), 50/60Hz
Power Consumption	5.0kW (7.6A per phase)



6MeV Model For illustration purposes only

SALES AND MANUFACTURING
 +44 (0)1502 500969 • sales@jme.co.uk



ALL GOODS AND SERVICES ARE SOLD SUBJECT TO THE TERMS AND CONDITIONS OF JME. A COPY OF THESE TERMS AND CONDITIONS IS AVAILABLE UPON REQUEST.

ALL BRAND NAMES AND PRODUCT NAMES WHERE USED ARE ACKNOWLEDGED TO BE TRADEMARKS OF THEIR RESPECTIVE HOLDERS.

NOTE: All dimensions/weights exclude X-Ray Generators/Gamma Projectors