



Portable Industrial LED Film Viewer

FV-2010 Plus

- ▶ **Electronic Light mask - World First**
- ▶ **Larger size: 400×100mm (15.8×4 inch)**
- ▶ **Low noise: Fan with temperature depended**
- ▶ **2 years free service guarantee**
- ▶ **CE Approved**

MAX.L=130,000Cd/m²

g=0.95

σ'=0.95

Characteristic:

- Luminance : 130,000Cd/m² (408,200Lux)
- Uniformity: 0.95 , Diffusion factor:0.95
- Window Size: 400×100mm (15.8×4")
- Weight less than 4.0 Kg (8.8lbs)
- 12 hours continues maximum luminance,
Surface temperature rise ≤ 18℃
- Unlimited dimmer from 5%-100%
- Free 2 years service guarantee
- CE Approved

What is electronic light mask?

Traditionally we use a series of metallic light masks which are mount on the surface of film viewers. It is inconvenient when you replace the light masks when you want to change the size of light, and energy waste because it just mask the light where you do not need, but the entire light screen is still turn on.

Electronic light mask is electronics controlled, the light screen is divided into 6 parts, you can turn on or turn off each parts of light screen by press one key. With the help of it, you just turn on the area you need, it will be convenient when you change the size of light, low heat and low energy cost.

The size of light will be switched as below:



Spare parts list:

Description	Quantity
Power adaptor & Line	1
Foot pedal	1
Light mask (15.8×2.7")	1
Instruction (English)	1
Guarantee and report (English)	1

Specification:

Max Luminance: ≥ 130,000Cd/M ² (408,200Lux)	Uniformity: g=0.95
Diffusion Factor: σ'=0.95	Viewer window: 400×100mm (15.8×4 inch)
Surface temp. rise ≤ 18℃ After 12 hours continues maximum luminance	Power: 85-264VAC 47~63Hz. (Full range)
Dimension: 600×80×160mm 23.6×3.1×6.3 inch (L×W×H)	Weight: 4Kg (8.8 lbs)

LCNDT 鹿成

www.Lcndt.net[®]



ISO9001 Registered

PRODUCT CERTIFICATE

PRODUCT	Industrial LED film viewer
MODEL	FV-2010 Plus
SERIAL NO.	101060
MEASUREMENT BASED ON	EN 25580 / ISO 5580
MEASUREMENT RESULT	QC Passed

Testing Report:

Maximum Luminance: 130,000Cd/M² Uniformity g: 0.95

Diffusion factor σ' : 0.95 Maximum Reading Density: 4.1 H/D

Film Density	ASTM/EN/ISO MIN. Cd/m ²	TEST MAX. Cd/m ²
2.21	30	726.70
2.72	10	213.20
3.66	10	24.70
4.29	10	7.60

NOTE: The luminance mentioned in above table is measured light through the film.



INSPECTOR INSPECTOR 3

MANAGER INSPECTOR 1

Date of Measurement: 2014.10.27

Lu Cheng NDT Equipment Corp.

E-mail: Sales@Lcndt.net (For sales) gm@Lcndt.net (For service)

Http: [//www.Lcndt.net](http://www.Lcndt.net)

Phone: 86-577-88293040 Fax: 86-577-88259689